

# Quick Reference Specification Sheet

## 4G 52mm Fabric Innerduct



MaxCell™ is a flexible fabric innerduct system designed specifically for increasing efficient cable deployments. The unique textile construction allows MaxCell™ to conform to the shape of cables placed within, greatly reducing wasted space.

### Technical Information

Material Fabric	Warp - Polyester Monofilament Filling - Nylon/Polyester
Material Pull Tape	High Tenacity Multifilament Polyester 565kg (5.54kN) / Optional 1135kg (11.13kN)
Sewing Line	High Tensile Polyester
Temperature range	-30°C to 100°C
Lubricate	100% Silicon Oil
Friction	-75% Lower Resistance
Breaking Tensile#	1 Cell >510kgs 2 Cell >938kgs 3 Cell >1366kgs
% Elongation @ 50kgs	<5%
Melting Point	>215°C
Thermal Expansion	8.4mm/100m/5°C
Detectable Wire	Optional AWG 18Ga. (0.75mm <sup>2</sup> ) Solid Core Copper with Vinyl and Nylon Insulation
Reel Length	2500m (Standard) Min 150m/ Max 5700m (3 cell)
Chemical Resistance**	Resistance to ground chemicals and petroleum products

# According to ASTM D5035.

\*\* Refer to 4G Technical Manual for more details

### Key Features

- Configurations in 1, 2, and 3 cells to match network requirements
- Available in Standard, Detectable, and Fire Resistant versions
- Pre-installed color-coded pulling tapes are standard
- Pre-lubricated for lower pulling tensions

#### Standard

4G 5222-1*	1 Cell Standard
4G 5222-2*	2 Cell Standard
4G 5222-3*	3 Cell Standard

#### Detectable

4G D5222-1*	1 Cell Detectable
4G D5222-2*	2 Cell Detectable
4G D5222-3*	3 Cell Detectable

#### Application

Minimum Duct/Conduit ID: 50mm  
Maximum cable diameter for each Cell: 22mm  
See Design Manual for Overlay and Multiple packs installation.

#### Accessories

##### Milliken Pull Tapes (Standard)

MT565-xx	565kg Pull Tape
MT815-xx	815kg Pull Tape
MT1135-xx	1135kg Pull Tape

##### Milliken Pull Tapes (Detectable)

DT565-xx	565kg Pull Tape
DT815-xx	815kg Pull Tape
DT1135-xx	1135kg Pull Tape

#### Tools for Installation

Swivel	Pull Tape
Scissors	Extra Lubricant
Vinyl Tape	Cable grip

\* Designate color of thread RD (Red), BK(Black), BL(Blue), YL(Yellow)

xx Designate spool length 900 (900m spool), 1500 (1500m spool)

Milliken Design, Inc.  
PO Box 220, Belfield NSW Australia  
Ph. +61 2 97035410  
MillikenInfraSol@milliken.com  
www.maxcell.com.au

